

HPLC Column Heater

HPLC Column Heater



HPLC CH-300



HPLC CH-600



HPLC CH-900

This instrument is used to stably and precisely control the temperature of analysis thus sensitivity, separation of peaks, analysis time of the chromatography management can be improved to ensure the accuracy and reproducibility of sample results.

HPLC Ch-300 (500) Column Heater

Features

- Unified design allows the column flexible arrangement of horizontal or vertical setting.
- Accurate temperature control and display: Two 4-digit LED display can ensure temperature control accuracy to $\pm 0.1^{\circ}\text{C}$.
- Fast and easy column installation: Magnetic elements create easy opening and closing of the column heater cover.
- Easy for observation: Transparent window allows clear view inside the HPLC column.
- Safe anti-leaking design: A container placed under heating chamber can prevent liquid from leaking.
- Flexible column placement: Provide stainless clamp holder inside heating chamber to make it easy for installing the column under heat.
- Smooth pipe: Provide smooth connection between input and output ports to guarantee that liquid can pass through.
- Stable column heater base: Provide additional large size base that can be mounted with column heater when required to stabilize the column heater.
- Convenient sample inserting valve component kits that can be fixed at any height of the column heater.

Model	HPLC CH-300 (500) Column Heater
Temperature Range	Room temperature to 100°C
Max Temperature	110°C
Temperature Increment	$\pm 0.1^{\circ}\text{C}$
Temperature Control Accuracy	$\pm 0.1^{\circ}\text{C}$
Temperature Stability	$\pm 0.1^{\circ}\text{C}$
Display	4-digit LED Actual Temperature Display (Red) 4-digit LED Set Temperature Display (Green)
Power Consumption	125W (CH-300) 160W (CH-500)
External Dimensions (W × D × H)	CH-300: 64mm × 105mm × 490mm CH-500: 110mm × 105mm × 540mm
Column Dimensions (W × D × H)	CH-300: 45mm × 33mm × 360mm CH-500: 82mm × 33mm × 400mm

HPLC CH-600 Column Heater

- Super size column heater: Ambient size 145mm × 380mm × 110mm (W × H × D)
- Three options of column height
- A powerful fan that can speed up the heating process and make complete circulation of the heat.
- Accurate temperature control and display: Microprocessor-controlled temperature device allows temperature accuracy to ±1°C.
- Easy installation with magnetic door frame.
- Easy for observation: Transparent window is easy for monitoring the heating process.
- Safe anti-leaking design: A container placed under heating chamber can prevent liquid from leaking
- Smooth pipe: Provide smooth connection between input and output ports to guarantee that liquid can pass through.

Model	HPLC CH-600 Column Heater
Temperature Range	Room temperature to 75°C
Max Temperature	85°C
Temperature Increment	±1°C
Temperature Control Accuracy	±0.3°C
Temperature Stability	±0.2°C
Display	3-digit LED Actual Temperature Display (Red) 3-digit LED Set Temperature Display (Green)
Power Consumption	300W
External Dimensions (W × D × H)	185mm × 172mm × 530mm
Column Dimensions (W × D × H)	145mm × 110mm × 380mm

HPLC CH-900 Column Heater

- Powerful: Powerful cooling function enables temperature inside the heating chamber to lower than room temperature by 25°C.
- Convenient for use with temperature setting knob and LED display of actual temperature.
- Accurate: Experiments show temperature accuracy of ±0.3°C and better.
- Intelligent: The temperature controlling system can automatically choose to heat or to cool based on the room and set temperature.
- Flexible: Easy installation of temperature control unit to be suitable for vertical or horizontal arrangement of the column heater.
- Unified design enables convenient matching with HPLC system.

Model	HPLC CH-900 Column Heater
Temperature Range	25°C below room temperature to 75°C
Max Temperature	80°C
Temperature Increment	±1°C
Temperature Control Accuracy	±0.5°C
Temperature Stability	±0.3°C
Display	3-digit LED Actual Temperature Display
Power Consumption	150W
External Dimensions (W × D × H)	185mm × 108mm × 490mm
Column Dimensions (W × D × H)	45mm × 26mm × 330mm

CROMTECH INDIA

1st Floor Begum Niwas, Opp Mercantile, Bank Society Colony, 5th Natwar Nagar Road, Jogeshwari (East), Mumbai 400 060.
 Maharashtra - India.
 Mobile: +91 98693 82134 / 81088 13320
 Telefax: +91 22 2838 6028
 Email: cromamumbai@mail.com / cromtechindia@mail.com / info@cromtechindia.com / sales@cromtechindia.com
 Website: www.cromtechindia.com